Burnout Clean-up Filter Driers (Solid Core)

SKY Part No.	Connection	Lay-in length	Diameter	Capacity kW R-22/410A	Capacity kW R-404A	Capacity kW R-134A
303-083	3/8 MSAE - Dual Access	146	64	6	4.5	3.5
303-163	3/8 MSAE - Dual Access	170	78	13	8	5.5
303-164	1/2 MSAE - Dual Access	177	78	15	8.5	6
303-165	5/8 MSAE - Dual Access	186	78	20	13	9.5
303-305	5/8 MSAE - Dual Access	259	78	18	15	12.5
303-306	3/4 MSAE - Dual Access	238	78	22	19	14
303-083S	3/8 SOL - Dual Access	146	64	6	4.5	3.5
303-163S	3/8 SOL - Dual Access	159	78	15	8.5	6
303-164S	1/2 SOL - Dual Access	162	78	15	8.5	6
303-165S	5/8 SOL - Dual Access	160	78	20	13	9.5
303-306S	3/4 SOL - Dual Access	239	78	22	19	14
303-307S	7/8 SOL - Dual Access	245	78	26	22	16
303-309S	1-1/8 SOL - Dual Access	245	78	31	27	20

Pancake

SKY Part No.	Connection	Lay-in length	Diameter	Capacity kW R-22/410A	Capacity kW R-404A	Capacity kW R-134A
303P-405S	5/8 ID - Dual Access	108	88	18	16	13
303P-406S	3/4 ID - Dual Access	108	88	21	20	17
303P-407S	7/8 ID - Dual Access	108	88	24	20	17
303P-409S	1-1/8 ID - Dual Access	118	88	28	24	21

KEY FEATURES

Manufactured in accordance with ISO/AS 5149.2, with a SWP of 3,200 kpa

- Solid core block of 60% MS/ 35% AL/ 5% AC, for the ultimate in acid, wax and moisture take-up, capacity and retention
- Membrane filter element will remove and retain all harmful particles.
- Anti-corrosion powder coat finish with chrome flare or solid copper connections, for ease of installation and increased service life.
- Dual access ports to monitor Pd and contaminant take up.