GLO-STICK®
UV Dye Injection System

SINGLE-DOSE CAPSULE

Key Benefits:

- Convenient, mess-free single-dose capsules
- Add refrigerant and dye in one simple step
- Works in all AC&R systems, **up to 450 PSI**
- Patented leak detection dye technology

Works with All Popular Refrigerants & Lubricants including A3 & A2L

OEM GRADE — Engineered to Meet Manufacturers' Specs

System Safe, Non-Flammable or Toxic

Brightest Dye on the Market!

UV LED — 400 nm UV LED

3x AAA — Batteries Included

Fluorescence Enhancing

GLO-AWAY™ Plus +

Service Labels

SPE-HVLGSE
GLO-STICK® COMPLETE Leak Detection Kit

SPE-HVL-CS	UV LED (400 nm) leak detection lamp
(1) SPE-GS1E	0.5 oz (15 ml) universal/POE dye capsule
(2) SPE-GS2E	0.5 oz (15 ml) universal/POE dye capsule
(1) SPE-GS3E	0.5 oz (15 ml) universal/POE dye capsule
RP-BV-50	Bleed valve
RP-EZ-25	8 in (20 cm) EZ-Ject™ hose assembly
RP-UVS-40	Fluorescence-enhancing glasses
RP-GA-2	2 oz (60 ml) GLO-AWAY™ Plus dye cleaner
RP-AD-410A	R-410a adapter/purge fitting
N/A	Purge capsule

NSF — Universal/POE Dye:
NSF Registered to meet food-grade processing requirements for category codes HTX2 and HX-2

SPE-GS1E-CS
GLO-STICK® 1E UV Dye

- 0.5 oz (15 ml) universal/POE dye capsule
- Treats up to:
  Lubricant: 1.6 qt (1.5 L)
  Refrigerant: 4.9 lb (2.2 kg)
  Cooling: 2 tons (7 kW)
  Horse Power: 4 Hp
- Requires bleed valve for injection (RP-BV-50)

SPE-GS2E-CS
GLO-STICK® 2E UV Dye

- 0.5 oz (15 ml) universal/POE dye capsule
- Treats:
  Lubricant: 1.7 to 3.2 qt (1.6 to 3 L)
  Refrigerant: 5 to 9.9 lb (2.3 to 4.5 kg)
  Cooling: 6 tons (21.1 kW)
  Horse Power: 4.1 to 10 Hp
- Requires bleed valve for injection (RP-BV-50)

SPE-GS3E-CS
GLO-STICK® 3E UV Dye

- 0.5 oz (15 ml) universal/POE dye capsule
- Treats:
  Lubricant: 3.3 qt to 2 gal (3.1 to 7.6 L)
  Refrigerant: 10 to 25 lb (4.6 to 11.3 kg)
  Cooling: 12 tons (42.2 kW)
  Horse Power: 10.1 to 25 Hp
- Requires bleed valve for injection (RP-BV-50)